

## Product Specifications

### Panel Characteristics

Front Panel Steel Plate Cold Rolled Commercial, 1.5mm thickness with Black Color (RAL9005) painted

Support Bar Steel Plate Cold Rolled Commercial, 1.5mm thickness with Black Color (RAL9005) painted

Rear Panel Steel Plate Cold Rolled Commercial, 1.5mm thickness with 5 to 8um Nickel painted

Panel Color Black Color Varnish Painted (RAL 9005)

Effective U Space 1U - 24PORT

Mounting Type Rack Mounted

Jack Bracket Set ABS, UL 94V-0

PCB FR4, UL 94V-0

Insertion Force 30N max (IEC 60603-7-5)

Retention Strength 7.7 Kgs between Jack and Plug

Operating Temperature -10°C to 60°C (ISO/IEC 11801, ANSI/TIA/EIA-568-C.2)


### Dimensions

Height (in/mm) 1,75in / 44,4mm - 24PORT

External Width (in/mm) 19,22in / 488,2mm

Depth (in/mm) 3,66in / 93mm - 24PORT

Includes 4 M5 x L12mm screw set

			
DATE: JUN 2014		DRAWING: ZARRAGA	
DRAWING: ZARRAGA			
ITEM N°: AW192NXT40			
DES : Modular Patch Panel 24 port for RJ45 Keystone Jack			
SHEET	1 OF 1	SCALE	1 : 2