

Cat.6A rack mount patch panel

Modular, shielded, keystone frame



Related products










NAWPNEL6A24



This modular patch panel is designed to be used with category 6A shielded connectors used in 10- Gigabit ethernet installations and exceeds ANSI/TIA/EIA-568 C.2 standards. With its protective shielding, crosstalk and electromagnetic interference are virtually eliminated in the unit, protecting vital network terminations. Designed to mount to any standard 19-inch horizontal rack or cabinet, this panel is offered in a 24-port configuration. A black powder painting coat finish gives the patch panel a sleek, elegant look. The patch panel includes an overall metal shield that provides a conductive path to ground that is provided by a 18 AWG terminal green / yellow cable, which meets the requirements of IEEE 802.3af and IEEE 802.3at for Power-over- Ethernet applications (PoE).



www.nexxtsolutions.com

Nexxt Solutions® ("Nexxt") is a registered trademark. Nexxt reserves the right to change any specifications without prior notice. The information contained in this product sheet is the proprietary property of Nexxt, and may not be used, reproduced or disclosed to others, in whole or in part, without written authorization of Nexxt. Although Nexxt has taken precautions to ensure the accuracy of the product specifications at the time of publication, however, we cannot be responsible for the errors, omissions, or changes due to obsolescence. If you would like to know more about our products, please visit our website at www.NexxtSolutions.com.



Cat.6A rack mount patch panel

Modular, shielded, keystone frame

Product specifications	Panel characteristics
Number of ports	24
Front panel	SPCC 1.5mm thickness with Black finish (RAL 9005)
Support bar	SPCC 1.5mm thickness with Black finish (RAL 9005)
Rear panel	SPCC 1.5mm thickness with 5 to 8um nickel finish
Ground cable	18AWG wire, with green/yellow striped color, length 40cm
Panel color	Black varnish paint (RAL 9005)
Effective U space	1U
Mounting type	Rack mounted
Insertion force	30N max (IEC 60603-7-5)
Retention strength	7.7 Kgs between jack and plug
Operating temperature	-10°C to 60°C (ISO/IEC 11801, ANSI/TIA/EIA-568-C.2)
	Dimensions
Height	1,75in
External width	19,22in
Depth	3,66in
Includes	4 M5 x L12mm screw set
	Electrical characteristics
Voltage rating	300V
Temperature rating	75°C
	Certifications and standards
International standards	ANSI/TIA/EIA-568-C.2, ISO/IEC 11801
ETL certificate	101002179CRT-001a
	Miscellaneous
MPN	NAW-PNEL6A24
UPC	798302033474
Labeling	NEXXT SOLUTIONS CAT 6A
Packaging	Carton Box
Quantity per bag	1 unit
Cu.ft.	2.82 per 15units
Warranty	5 year limited warranty. For full warranty details, visit: https://www.nexxtsolutions.com/warranty









www.nexxtsolutions.com

Nexxt Solutions® ("Nexxt") is a registered trademark. Nexxt reserves the right to change any specifications without prior notice. The information contained in this product sheet is the proprietary property of Nexxt, and may not be used, reproduced or disclosed to others, in whole or in part, without written authorization of Nexxt. Although Nexxt has taken precautions to ensure the accuracy of the product specifications at the time of publication, however, we cannot be responsible for the errors, omissions, or changes due to obsolescence. If you would like to know more about our products, please visit our website at www.NexxtSolutions.com.