

Wall fixed cabinet

Fully assembled

4U/6U/9U/12U - 450mm/600mm



NEC-F4U64B
NEC-F6U64B
NEC-F9U64B
NEC-F12U64B

NEC-F4U66B
NEC-F6U66B
NEC-F9U66B
NEC-F12U66B

Related products



AW220NXT07



AW220NXT21



AW220NXT95

Nexxt Solutions Essential Wall Mount Fixed assembly enclosures are ideal for installations where space is limited, or a full cabinet solution is not required. These wall mount units are housed in a lockable heavy-gauge metal enclosure, to keep network equipment and cables safe and properly organized. Available in 4, 6, 9, and 12 rack spaces, these enclosures are designed for mounting multiple patch panels and diverse network, voice, and data devices. Easy to install and assemble, our wall mount cabinets offer a cost-effective solution for applications requiring flexibility, reliability, and cable management capabilities.

Highlights:

- 132lb maximum static load capacity
- Frame construction reinforced with steel, specially made to support heavy equipment
- Lockable access to front glass door
- Convenient side panels are easy to remove for maintenance
- Standard square-punched mounting rails for faster equipment loading
- The front door can turn 270 degrees
- 2 spaces for optional fan units**
- Tool less, reversible glass door installation
- EIA-compliant mounting rail system can be easily adjusted to accommodate equipment of varying depths
- U-rack units numbered on the front and back sections simplify installation
- Finished surface prevents damage caused by rust and other external factors

www.nexxtsolutions.com

Nexxt Solutions® ("Nexxt") is a registered trademark. Nexxt reserves the right to change any specifications without prior notice. The information contained in this product sheet is the property of Nexxt, and may not be used, reproduced, or disclosed to others, in whole or in part, without written authorization by Nexxt. Although Nexxt has taken precautions to ensure the accuracy of the product specifications at the time of publication, we cannot be responsible for the errors, omissions, or changes due to obsolescence. If you would like to know more about our products, please visit our website at www.NexxtSolutions.com.

Wall fixed cabinet

Fully assembled

4U/6U/9U/12U - 450mm/600mm

Technical specifications | 450mm

Wall mount enclosure characteristics

Color	Black varnish paint (RAL 9005)			
Effective U space	4U	6U	9U	12U
Structure type	Assembled rack			
Mounting type	Wall mounted, fixed			
Access type	Side removable panels Front door and rear panel			
Material (main body)	SPCC*, 19 gauge			
Material (mounting angles)	SPCC*, 16 gauge			
Active ventilation	Space for 2 ventilation units**			
Passive ventilation	Perforated front and rear doors at 0% Top and bottom ventilation access			
Protection grade	IP20 IK00			

Dimensions

External height	10.28in/261mm	13.78in/350mm	19.02in/483mm	24.29in/617mm
Internal height	6.97in/177mm	10.51in/266mm	15.75in/400mm	20.98in/533mm
External width	23.62in/600mm			
Internal width	19in/483mm			
External depth	17.72in/450mm			
Max. device depth	12.95in/329mm			
Static load capacity	132lb/60kg			
Front door spin degree	Can turn up to 270 degrees			
Includes	1 top panel 1 bottom panel 2 frames 1 front glass door 1 rear panel 2 side panels 2 L-shaped brackets 1 mounting bracket 4 vertical rails Assembly hardware kit User hardware kit Installation manual			

Dimensions

International standards	RoHs, Reach
Certifications and approvals	IEC297-2, DIN41491, BSI5954, DIN41494, EXT ANSI/EIARS-310-D GB/T3047.2-92BZ; 19", Metric standard, ETSI standard

Miscellaneous

MPN	NEC-F4U64B	NEC-F6U64B	NEC-F9U64B	NEC-F12U64B
UPC	798302037182	798302037199	798302037205	798302037212
Labeling	NEXXT SOLUTIONS			
Packaging	Assembled package (PE bag + carton)			
Cu. ft	3.00	3.96	5.40	6.79
Warranty	5-year limited warranty***			

*SPCC: Commercial grade, cold rolled steel sheets

**Fans not included in the box

*** For warranty details, visit /www.nexxtsolutions.com/warranty

Wall fixed cabinet

Fully assembled

4U/6U/9U/12U - 450mm/600mm

Technical specifications | 600mm

Wall mount enclosure characteristics

Color	Black varnish paint (RAL 9005)			
Effective U space	4U	6U	9U	12U
Structure type	Assembled rack			
Mounting type	Wall mounted, fixed			
Access type	Side removable panels Front door and rear panel			
Material (main body)	SPCC*, 19 gauge			
Material (mounting angles)	SPCC*, 16 gauge			
Active ventilation	Space for 2 ventilation units**			
Passive ventilation	Perforated front and rear doors at 0% Top and bottom ventilation access			
Protection grade	IP20 IK00			

Dimensions

External height	10.28in/261mm	13.78in/350mm	19.02in/483mm	24.29in/617mm
Internal height	6.97in/177mm	10.51in/266mm	15.75in/400mm	20.98in/533mm
External width	23.62in/600mm			
Internal width	19in/483mm			
External depth	23.62in/600mm			
Max. device depth	18.82in/479mm			
Static load capacity	132lb/60kg			
Front door spin degree	Can turn up to 270 degrees			
Includes	1 top panel 1 bottom panel 2 frames 1 front glass door 1 rear panel 2 side panels 2 L-shaped brackets 1 mounting bracket 4 vertical rails Assembly hardware kit User hardware kit Installation manual			

Dimensions

International standards	RoHs, Reach
Certifications and approvals	IEC297-2, DIN41491, BSI5954, DIN41494, EXT ANSI/EIARS-310-D GB/T3047.2-92BZ; 19", Metric standard, ETSI standard

Miscellaneous

MPN	NEC-F4U66B	NEC-F6U66B	NEC-F9U66B	NEC-F12U66B
UPC	798302037229	798302037236	798302037243	798302037250
Labeling	NEXXT SOLUTIONS			
Packaging	Assembled package (PE bag + carton)			
Cu. ft	3.93	5.19	7.08	8.91
Warranty	5-year limited warranty***			

*SPCC: Commercial grade, cold rolled steel sheets

**Fans not included in the box

*** For warranty details, visit www.nexxtsolutions.com/warranty

