


NXK-UTG00

## Related products











PCGPCC6ALZ\*\*BL

AW160NXT\*\*

AW192NXT4\*







Product specifications	
	Connector characteristics
RJ45 jack housing and contact bracket	ABS + PC, UL 94V-0. gray color. PC, UL 94V-2 clear
(1)	
RJ45 jack contact material and finish (2)	Phosphor bronze with nickel plated. 50 micro-inch gold plated on plug contact area
Cap (3)	ABS+PC UL 94V-0, black color
IDC housing and terminal (4)	PC, grey color (RAL7035), UL 94V-2. Phosphor bronze with tin plated
Toolfree cap material (5)	PC white color, UL 94V-2
Shutter (6)	ABC+PC, white color, UL 94V-0
PCB (7)	FR4, UL 94V-0
Insertion force	20N max (IEC 60603-7-4)
Retention strength	7.7 kg between jack and plug
Durability	Jack: 750 cycles plug-jack mating and unmating test, insertion cycles at 20 cycles/mi-
	nute max. Contact resistance test per 100 cycles (ISO/IEC 11801, IEC 60603-7-4)
Wiring	T568A and T568B
Operating temperature	-10°C to 60°C (ISO/IEC 11801, ANSI/TIA/EIA-568-C.2)
	Transmission characteristics
Transmission speed	10,000Mbps
Bandwidth	500MHz
	Certifications and standards
International standards	ANSI/TIA/EIA-568-C.2, ISO/IEC 11801, IEC 60603-7-4
UL certificate	20080124 – E318655 DUXR.E318655
ETL certificate	Yes
	Miscellaneous
MPN	NXK-UTG00
UPC	798302036055
Labeling	NEXXT SOLUTIONS CAT 6A
Packaging	Plastic bag
Quantity per bag	
Cu.ft	1,70 per 100 units
Warranty	Lifetime limited warranty*



or changes due to obsolescence. If you would like to know more about our products, please visit our website at <a href="www.NexxtSolutions.com">www.NexxtSolutions.com</a>.



disclosed to others, in whole or in part, without written authorization of Nexxt. Although Nexxt has taken precautions at the time of publication, however, we cannot be responsible for the errors, omissions,



