

Fixed wall-mounted enclosures 4U, 6U, 9U, 12U, 15U and 18U Semi-knocked down (SKD)

Nexxt Solutions semi-knocked down (SKD) fixed wall mount enclosures are ideal for installations where space is limited or where a full cabinet is not required. Our wall mount enclosures are the perfect solution for any 19-inch installation. Commonly used with all patch panels and cable management panels to give installations an organized, protected and professional appearance. These wall mount enclosures come as semi-knock down version. Available with 4, 6, 9, 12, 15 and 18 rack spaces.



4U

PCRWESKD04U60FXBK
PCRWESKD06U60FXBK
PCRWESKD09U60FXBK
PCRWESKD12U60FXBK
PCRWESKD15U60FXBK
PCRWESKD18U60FXBK



18U



15U



9U



12U



6U

- Available to accommodate EIA industry-standard 19-inch panels
- Follows ANSI/TIA/EIA-568 C.2 manufacturing standards and meets ANSI/EIA RS-310-D. It also complies with IEC297-2; DIN41491: PART1; DIN41494: PART7; GB/T3047.2-92 standard
- Single section structure, the turning angle of front door is above 180 degree
- 19-inch standard installation provides easy access for management and maintenance
- One layer of electrostatic coating protects it against humidity, rust, scratches, peeling, strong acid and alkaline erosion
- Black epoxy-polyester hybrid powder paint
- For indoor use only, in environmentally controlled areas, may not be used outdoors, in industrial or harsh environments or in plenum spaces
- Use with shelves or rails to support small modular network or voice switches routers and other network equipment
- Universal horizontal cable manager
- Horizontal power strips can be fit
- Front glass door and side panels with key lock sets
- Pathway for routing cables located on the top and bottom panels
- Adjustable vertical rails
- Attached grounding bolts
- Protection grade: IP20
- Max load: 132lb

Fixed wall-mounted enclosures 4U, 6U, 9U, 12U, 15U and 18U Semi-knocked down (SKD)

Product specifications

Wall mount enclosure characteristics	
Enclosure color	Black varnish paint (RAL 9005)
Effective U space	4U 6U 9U 12U 15U 18U
Structure type	Semi-knocked down (SKD)
Mounting type	Wall mounted
Access type	Fixed
Material (main body)	SPCC, 1.2mm thickness (post frame, top and bottom panels, front door, rear and side panels)
Material (mounting angles)	SPCC, 1.2mm thickness
Ventilation access	For two fans (1 fan included)
Protection grade	IP20
Dimensions	
External height	10.83in 14.33in 19.57in 24.84in 30.00in 35.31in
Internal height	7.68in 11.18in 16.42in 21.69in 26.85in 32.17in
External width	23.62in
Internal width	19in
External depth	23.62in
Internal depth	21.62in
Load capacity	Can hold up to 132lb
Front door spin degree	Can turn up to 180 degrees
Includes	1 front glass door 1 rear panel 1 top panel 1 bottom panel/base 1 front frame 4 mounting perforated rails 2 side panels 1 bag of assembly accessories 1 installation guide
Certifications and standards	
International standards	UL 60950 or UL 60950-1, or UL 60950-21 as appropriate ANSI/TIA/EIA 568.C.2 ANSI/EIA RS-310-D. IEC297-2; DIN41491: PART1; DIN41494: PART7; GB/T3047.2-92
Miscellaneous	
MPN	PCRWESKD 04U60FXBK PCRWESKD 06U60FXBK PCRWESKD 09U60FXBK PCRWESKD 12U60FXBK PCRWESKD 15U60FXBK PCRWESKD 18U60FXBK
UPC	798302034815 798302034822 798302034839 798302034846 798302034853 798302034860
Labeling	NEXXT SOLUTIONS
Packaging	Semi-knocked down in a carton box
Cu.ft.	4.28 4.36 4.44 4.80 5.27 6.05
Warranty	5-year limited warranty. For full warranty details, visit: https://www.nexxtsolutions.com/warranty

SPCC: Commercial grade, cold rolled steel plate

