

Product: RTL8188C/8192C/8192D USB Software Package - Linux Driver
Version: v3.4.1_3418.20120217

Release History:

v2.0.939.20100726	<ol style="list-style-type: none"> 1. Use the bg mode when AP is in WEP and TKIP mode. (Recommended by latest WiFi 11n test plan). 2. First release.
v2.0.967.20100730	<ol style="list-style-type: none"> 1. Add functionality of Antenna diversity.
v2.0.974.20100803	<ol style="list-style-type: none"> 1. Fixed the Big Endian issue.
v2.0.1042.20100902	<ol style="list-style-type: none"> 1. Resolved static link issue with RTL8712U. 2. Fixed the Ad-hoc connection bug when the Ad-hoc ssid is the same with someone AP's SSID. 3. Update related PHY parameters to improve throughput. 4. Improve Antenna diversity algorithm.
v2.0.1126.20101020	<ol style="list-style-type: none"> 1. Added USB's selective suspend feature. 2. Added the Realtek GPL into each C and header files. 3. Added related ioctl command for Android platform. 4. Fixed NIC status display issue. 5. Fixed power training issue at station mode.
v2.0.1170.20101112	<ol style="list-style-type: none"> 1. Modify the CONFIG section of Android-x86 2. Fixed radius issue. 3. Update FW to V60. 4. Support the Power saving function. 5. Update usb_id_table to v38. 6. Fixed the kernel panic when receive WDS packet.
v2.0.1180.20101116	<ol style="list-style-type: none"> 1. Fixed compiler error.
v2.0.1212.20101205	<ol style="list-style-type: none"> 1. Fix the Android private wifi ioctl SCAN-ACTIVE, SCAN-PASSIVE 2. Alter the retry limit of "Active disconnect" to 8 3. Fix the overkilling problem of active disconnect caused by frequently site surveying 4. Fix the connect/disconnect looping problem on Android. 5. Removed the "scan interval" protection of site survey function temporarily 6. Adjust locking mechanism of TX, and fix race-condition issue.
v2.0.1212.20101208	<ol style="list-style-type: none"> 1. Add Kconfig.
v2.0.1324.20110126	<ol style="list-style-type: none"> 1. Synchronization strategy improved. 2. Fixed the AP Tx fragment issue when using the WPA2-RADIUS. 3. Added the IP header 8 bytes alignment. 4. Added new feature - Easy Replacement. 5. Added 20/40 MHz Coexistence test item (5.2.48 for wifi test) 6. Fixed related connection failure issue in Ad-hoc mode. 7. Updated usb_id_table to DID_USB_v47_20110118.
v2.0.1346.20110214	<ol style="list-style-type: none"> 1. Fixed Ad-hoc connection issues.
v2.0.1406.20110309	<ol style="list-style-type: none"> 1. Updated usb_id_table to DID_USB_V50_20110209.

	<ol style="list-style-type: none"> Fixed compile error in kernel 2.6.37 Fixed Ad-hoc issue with DLink-DWA130.
v3.0.1590.20110511	<ol style="list-style-type: none"> The version of usb_id_table is DID_USB_V60_20110425.
v3.0.1684.20110525	<ol style="list-style-type: none"> Add wps probe req ie & wps assoc resp ie for wps2.0 Patch issue_qos_nulldata()/issue_nulldata() to set tods/fromds bit field depend on sta mode, ap mpde, adhoc mode
v3.0.1759.20110601	<ol style="list-style-type: none"> Supported the WiFi Direct functionality. Supported the WPSv2.0 functionality. Updated the hostapd and wpa_supplicant for WiFi Direct and WPS v2.0.
v3.0.2028.20110629	<ol style="list-style-type: none"> Refine WiFi Direct. Support Android wifi cmd "COUNTRY" . Add HW antenna diversity function. Modified set wep key for auth SHARED mode. Modified key index for Broadcom IOT issue. Fixed Big Endian issue in amsdu_to_msdu(). Support more USB dongle (DID_USB_V71_20110628).
v3.0.2052.20110701	<ol style="list-style-type: none"> Fixed the problem of cannot power down. Support Android early suspend
v3.0.2164.20110715	<ol style="list-style-type: none"> Reset MCU while polling FW ready fail Refine of RX signal statistics Support combo scan.
v3.0.2230.20110728	<ol style="list-style-type: none"> WiFi Direct function improve. Refine power saving functions.
v3.1.2291.20110804	<ol style="list-style-type: none"> Fixed WPS ie parsing issue. Add an ioctl rtw_p2p_get_device_name() that can get peer devices' names. Refine ioctls' set/get forms that related to p2p.
v3.1.2497.20110906	<ol style="list-style-type: none"> For SoftAP mode, fixed WPS connecting issue with RALINK3070. Fixed the Big Endian Autoload check fail issue. Fixed the IOT issue with Cisco 802.1x ap.
v3.1.2590.20110922	<ol style="list-style-type: none"> Fixed incorrect LED behavior. Fixed a potential resource leaks. Fixed possible race condition when using incorrect lock.
v3.1.2590.20111020	<ol style="list-style-type: none"> Sync. WiFi_Direct_User_Interface to driver
v3.3.0_2971.20111128	<ol style="list-style-type: none"> Support both CU-series and DU-series Supported Linux kernel v3.0.2 Improved quality of Video over IP multicast Increase a functionality to support L2 Bridge Speed up hardware initialization process for CU-series Update android_reference_code Fixed some Endianness issues Fixed the IOT issue for Wi-Fi Direct connection, software AP and station mode Fix the roaming problem
v3.3.1_3083.20111213	<ol style="list-style-type: none"> Fix WEP SHARED connection problem.
v3.3.2_3192.20120103	<ol style="list-style-type: none"> Add android_reference_code_ICS to support Android 4.x Support scan with multiple SSID Fix problem of PMK caching

	<ul style="list-style-type: none">4. Fix problem of TKIP countermeasure5. Fix RX reordering mechanism
v3.4.0_3317.20120120	<ul style="list-style-type: none">1. Support NL80211 interface2. Support Android WiFi-Direct Framework
v3.4.1_3418.20120217	<ul style="list-style-type: none">1. Fix the problem of TX rate report using NL802112. Update android_reference_codes_ICS3. Fix some bugs of WiFi-Direct using NL802114. Fix the Wifi-Direct IOT issue with Samsung GS2

Description:

Realtek provides the solution for WLAN in hardware and software. The software package could be adopted for Realtek RTL8188C/8192C/8192D USB WLAN series hardware on Linux based platforms.

Software Version:

RTL8188C/8192C/8192D USB Linux Driver Version: v3.4.1_3418.20120217

Firmware Version:

Firmware is embedded in the RTL8188C/8192C/8192D USB driver.

The firmware version of RTL8192C is V79

The firmware version of RTL8192D is V25

Hardware Supported:**CU-series:**

- RTL8188CUS
- RTL8188RU
- RTL8188CUS-Slim Solo
- RTL8188CUS-Slim Combo
- RTL8188CE-VAU
- RTL8188CUS-VL
- RTL8188CTV
- RTL8192CUS
- RTL8192CE-VAU

DU-series:

- RTL8192DU-VS
- RTL8192DU-VC

Platform Supported:

- Linux (kernel 2.6.18 ~ 2.6.38 and kernel 3.0.2)
- Android 1.6 ~ 2.3, 4.0

CPU supported:

- x86
- ARM
- MIPS